




## DULUX SOLARSCREEN

### A339-LINE

<b>PRODUCT NAME</b>	<b>Dulux Solarscreen</b>				
<i>Product Code</i>	A339-Line				
<b>USAGE</b>	<p><b>Dulux Solarscreen</b> is a durable pigmented varnish based on a special resin for the decoration and protection for all types of new or previously painted wood surfaces. It has excellent abrasion resistance and highlights the natural beauty of the grain of the wood.</p> <p>It is a water resistant and flexible finish that provide long lasting protection. Its unique formulation filters out UV rays thereby minimising the traditional problems of cracking, flaking and peeling.</p>				
<b>PACK SIZE</b>	1 and 5 litres				
<b>COLOUR RANGE</b>	See appropriate Colour Card.				
<b>COMPOSITION (nominal)</b>	<p><i>Pigment</i> : Lightfast Non-Lead Pigments  <i>Binder</i> : Modified Alkyd  <i>Solvent</i> : White Spirit</p>				
<b>VOLUME SOLIDS</b>	38% (nominal).				
<b>DRYING TIMES</b>	<i>Single coat at standard thickness :</i>				
<i>Touch Dry</i>	1 - 2 hours				
<i>Recoat</i>	4 hours				
<b>FILM THICKNESSES</b>	<p><i>Wet</i> : 50 microns  <i>Dry</i> : 20 microns</p>				
<b>THEORETICAL COVERAGE</b>	Theoretical coverage which can be achieved under normal condition is 19m <sup>2</sup> /litre.				
<b>APPLICATION</b>					
<b>THINNING</b>					
<i>Brush Application</i>	<p>For sealing new or bare surfaces thin with up to 1 part of Dulux Thinner 850-41 or white spirit to 5 parts of paint (20%).</p> <p>For normal use thinning is not usually necessary.</p>				
<b>CLEANING UP</b>	Clean all equipment with Dulux Thinner 850-41 or white spirit immediately after use.				
<b>SURFACE PREPARATION</b>	Surfaces must be clean, dry and free from all defective or poorly adhering material, dirt, grease, wax etc. All surfaces should be thoroughly rubbed down in the direction of the grain, using a suitable abrasive paper and then dusted off.				
<b>SYSTEM INFORMATION</b>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; padding: 5px;"><i>Primer</i></td> <td style="width: 50%; padding: 5px;"><i>Finish (3 coats)</i></td> </tr> <tr> <td style="padding: 5px;">NA</td> <td style="padding: 5px;">Dulux Solarscreen (A339)</td> </tr> </table>	<i>Primer</i>	<i>Finish (3 coats)</i>	NA	Dulux Solarscreen (A339)
<i>Primer</i>	<i>Finish (3 coats)</i>				
NA	Dulux Solarscreen (A339)				
<b>FLASH POINT</b>	32°-55°C				

# DULUX SOLARSCREEN A339-LINE

## SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

### FLAMMABLE

Keep away from sources of ignition. No smoking.

Keep container tightly closed and keep out of reach of children.

Contains white spirit. Work only in areas of good ventilation. Inside always keep doors and windows fully open during application and drying. Do not use on large surface areas inside or in small confined spaces.

**IF THIS PRODUCT IS USED BY PROFESSIONAL OPERATORS** it may be applied by brush or roller to large surface areas inside or used in small confined spaces, providing air supplied breathing equipment is used. When applying for short periods only, a suitable cartridge mask may be worn providing the filter is changed regularly.

A suitable cartridge mask should also be worn when rubbing down.

All respiratory equipment must meet an appropriate approved standard.

When applying paint it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Use soap and water or a recognised skin cleaner to remove splashes from skin.

Care must be taken when transporting. Keep container in a secure upright position.

Contains no added lead or mercury.

Protect from extremes of temperature. Store in a cool place.

In the event of an accident contain and collect spillage using sand or earth.

Do not empty into drains or water courses.

Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.

For further information or if you have any concerns about using this product contact the Sales Department at the address below:

ICI Paints (Singapore) Pte Ltd  
22 Soon Lee Road Jurong  
Singapore 628082  
Tel: 2650677 Fax: (65) 2654775  
Website: <http://www.icipaints.com.sg>