


PRODUCT NAME <i>Product Code</i>	Dulux Pentalite Mouldguard A933-25664
USAGE	Dulux Pentalite Mouldguard is designed to prevent mould growth on all interior ceilings. It is the ideal choice for bathrooms, kitchens, bedrooms and anywhere where mould-free finish is desired. Dulux Pentalite Mouldguard is a good quality, durable emulsion with a smooth matt finish. It is suitable for all normal interior masonry surfaces including brickwork, plaster, coment, asbestos and soft wallboards.
PACK SIZE	5 litres
COLOUR RANGE	White
FILM PROPERTIES <i>Water Resistance</i>	Will tolerate the levels of atmospheric humidity normally present in interior environments and will withstand moderate washing.
COMPOSITION (nominal)	Pigment : Non-lead Pigments Binder : PVA Copolymer Emulsion Solvent : Water
VOLUME SOLIDS	30%
DRYING TIMES <i>Touch Dry</i> <i>Recoat</i>	Single coat at standard thickness: Dependent on temperature and humidity 1 - 2 hours
THEORETICAL COVERAGE	Theoretical coverage which can be achieved under normal conditions is 9-10m ² /litre.
APPLICATION	
THINNING <i>Brush or Roller</i>	Add up to 1 part of clean water to 10 parts of paint (10%).
<i>Conventional Spray</i>	Add up to 1 part of clean water to 6 parts of paint (15%).
<i>Airless Spray</i>	Add up to 1 part of clean water to 10 parts of paint (10%).
SPRAY RECOMMENDATIONS <i>Conventional Spray</i>	Satisfactory through most equipment.
<i>Airless Spray</i>	A typical set up for spray application would be a minimum working pressure on paint of 140 Kg/cm ² (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle 65°.
CLEANING UP	Clean all equipment with clean water immediately after use.
SURFACE PREPARATION	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi or algae with Dulux Fungicidal Wash (A980-19260). If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer (see below).

DULUX PENTALITE MOULDCUARD

A933-25664

SYSTEM INFORMATION

Powdery Surfaces

Sealer (1 coat)
Dulux Alkali Resisting Wall Primer Sealer
(A579-15054) thinned 10% with white spirit

Finish (2 coats)

Alkaline and New Surfaces

Dulux Acrylic Alkali Resisting Primer Sealer
(A931-1050)
or
Supercoat Alkali Resisting Wall Primer Sealer
(A931-25120)

Dulux Pentalite Mouldguard
(A933-25664)

Normal, Sound Surfaces

No sealer required

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Keep container in a secured, upright position and tightly closed and keep out of reach of children.

A suitable cartridge mask should be worn when rubbing down.

Ensure good ventilation during application and drying.

Do not breathe vapour/spray. In case of insufficient ventilation during spraying wear suitable respiratory equipment.

All respiratory equipment must meet an appropriate approved standard.

Keep away from food, drink and animal feeding stuff.

When applying paint, it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove splashes from skin; use soap and water or a recognised skin cleaner.

Care must be taken when transporting paint. Keep container in a secure upright position.

Contains no added lead or mercury.

Protect from extremes of temperature. Store in a cool place.

In the event of an accident, contain and collect spillage using sand or earth.

Do not empty into drains or water courses.

Dispose of any paint waste in accordance with appropriate Environmental Quality Regulations.

Safety datasheet available for professional users on request.

For further information or if you have any concerns about using this product, contact us at :

ICI Paints (Singapore) Pte Ltd
22 Soon Lee Road Jurong Singapore 628082
Tel: 6 2650677 Fax: (65)6 2654775
Website: www.icipaints.com.sg
Email: customer_care_sg@ici.com